



MSDS

(Material Safety Data Sheet)

SECTION #1 PRODUCT AND COMPANY IDENTIFICATION

TRADE NAME: **TOTAL QUARTZ INEO MC3, QUARTZ INEO 504/507, QUARTZ ENERGY 9000 0W-30, QUARTZ ENERGY 9000 5W-40, QUARTZ FUTURE 9000 5W-30, QUARTZ RACING 10W-50, QUARTZ 7000 10W-40 and QUARTZ 7000 15W-50**

CHEMICAL NAME AND SYNONYMS: MIXTURE

MANUFACTURER/SUPPLIER'S NAME: TOTAL LUBRICANTS CANADA INC.
220, LAFLEUR
LASALLE, QUEBEC
H8R 4C9
Tel.: (514) 595-7579 or 1-800-463-3955

24 HOURS EMERGENCY: Call CHEMTREC 1-800-424-9300 or 703-527-3887

PRODUCT USE: Gas engine oil

WHMIS CLASS AND DESCRIPTION -

This product is not regulated by the WHMIS.

SECTION #2 COMPOSITION/INFORMATION ON INGREDIENTS

NOM	%	No CAS
---	--	---

ADDITIONAL REGULATORY INFORMATION

- No hazardous ingredients as defined by the Canadian Hazardous Products Act (BILL C70) or by OSHA 29 CFR 1910.1200.
- Canadian DSL status: All ingredients are listed.
- * No components of this product have been found carcinogenic or potential carcinogen. Does not contain ingredients that are listed as carcinogenic or potential carcinogen by OSHA, IARC or the U.S. National Toxicology Program (NTP). This product or its components have no teratogenic or mutagenic effects known.

SECTION #3 PHYSICAL DATA

PHYSICAL STATE AT 25°C	Liquid
BOILING POINT:	> 250°C
POUR POINT:	< 20°C
DENSITY (g/cm ³ at 15°C):	0,87 to 0,89
VAPOR PRESSURE (mm Hg at 20°C):	Negligible
VISCOSITY (cSt at 100°C):	10 to 21
EVAPORATION RATE:	Negligible
SOLUBILITY IN WATER:	Negligible
APPEARANCE ET ODOR:	Amber liquid with characteristic odor

SECTION #4 STABILITY AND REACTIVITY

STABILITY:	Stable
CONDITIONS TO AVOID:	Avoid excessive heat, open flames and formation of oil mist.
PRODUCTS TO AVOID:	Oxidizing agents, strong acids and bases.
HAZARDOUS DECOMPOSITION PRODUCTS:	N/A
POLYMERIZATION:	Will not occur

SECTION #5 FIRE FIGHTING MEASURES

FLASH POINT (COC):	> 200°C
FLAMMABILITY LIMITS IN AIR:	LEL: N/A
(% PER VOLUME)	UEL: N/A
AUTOIGNITION TEMPERATURE (°C):	N/A
EXTINGUISHING MEDIA:	Foam, Dry chemical and CO ₂
HAZARDOUS COMBUSTION PRODUCTS:	Normal combustion products, CO and CO ₂ .
SPECIAL FIRE FIGHTING PROCEDURES:	Do not enter confined fire space without adequate protective clothing and an approved positive self-contained breathing apparatus. Use water to cool fire exposed containers.

SECTION #6 TOXICOLOGICAL INFORMATION

SPECIES	LD ₅₀ ORAL	LD ₅₀ DERMAL	LC ₅₀ INHALATION	HRS
Rat	> 5000 mg/Kg	> 2000 mg/Kg	N/A	---

INHALATION: Prolonged exposure to high vapor concentration of this product can cause headache, dizziness and nausea. Short-term overexposure can cause an irritation to the respiratory passages.
Exposure limit to the mist = 5 mg/m³ (TLV/TWA, ACGIH).

CONTACT WITH EYES: May cause eye irritation.

SKIN CONTACT: This product should not cause skin irritation. Prolonged and repeated contact with this product can cause skin drying, which may result in skin irritation and dermatitis.

INGESTION: May cause nausea.

SECTION #7 ACCIDENTAL RELEASE MEASURES

SPILL AND LEAK PROCEDURES: Eliminate all ignition sources. Stop leak only if safe to do so. Absorb residue or small spills with absorbent material and remove to non-leaking containers for disposal.

SECTION #8 HANDLING AND STORAGE

STORAGE AND HANDLING: Store in cool, dry, ventilated area, away from heat and ignition sources. Use good personal hygiene. Always keep the container close.

SECTION #9 EXPOSURE CONTROLS / PERSONAL PROTECTION

VENTILATION: Mechanical ventilation is recommended.

RESPIRATORY PROTECTION: If mist present, chemical cartridge respirator is recommended.

GLOVES: Resistant gloves (Viton, Nitrile, Neoprene) are recommended when handling this material.

EYE PROTECTION: Chemical safety goggles are recommended.

OTHER PROTECTION: In confined spaces or where the risk of skin exposure is higher, resistant clothing or apron should be worn.

SECTION #10 DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHODS: Consult relevant local authorities. Reclaim or dispose of at a licensed waste disposal company. Incinerate with approval of appropriate local authority.

SECTION #11 FIRST AID

INHALATION: Remove person to fresh air. See a physician if irritation persists.

CONTACT WITH EYES: Flush immediately with water for at least 15 minutes.

CONTACT WITH SKIN: Wash contaminated skin with mild soap and water. See a physician if irritation persists.

INGESTION: This product has a low toxicity. May cause nausea and have a laxative effect. Do not induce vomiting. Contact an Anti-Poison Center (1-800-463-5060).

SECTION #12 HAZARDS IDENTIFICATION

INHALATION: Prolonged exposure to high vapor concentration of this product can cause headache, dizziness and nausea. Short-term overexposure can cause an irritation to the respiratory passages.
Exposure limit to the mist = 5 mg/m³ (TLV/TWA, ACGIH).

CONTACT WITH EYES: May cause eye irritation.

SKIN CONTACT: This product should not cause skin irritation. Prolonged and repeated contact with this product can cause skin drying, which may result in skin irritation and dermatitis.

INGESTION: May cause nausea.

SECTION #13 ECOLOGICAL INFORMATION

ENVIRONMENTAL EFFECTS:

Do not allow product or runoff from fire control to enter storm or sanitary sewers, lakes, rivers, streams, or public waterways. Block off drains and ditches. Provincial regulations require and federal regulations may require that environmental and/or other agencies be notified of a spill incident. Spill area must be cleaned and restored to original condition or to the satisfaction of authorities.

BIODEGRADABILITY: NOT READILY BIODEGRADABLE.

