

FLUIDE SYN FE



SYNTHETIC AUTOMATIC TRANSMISSION FLUID

USES

- Automatic transmissions and torque converters of commercial vehicles and industrial vehicles.
- When the manufacturer requires an ATF (Automatic Transmission Fluid) meeting GM DEXRON®-IIE.

PROPERTIES

- Very high viscosity index.
- Very low pour point.
- Excellent resistance to oxidation.
- Extended drain interval.
- Fuel saving.

CHARACTERISTICS

FLUIDE SYN FE	Unit	
Volumetric mass at 15°C	kg/m ³	840
Colour	-	Red
Viscosity at 40°C	mm ² /s	33
Viscosity at 100°C	mm ² /s	7,4
Viscosity index	-	200
Viscosity Brookfield at -40°C	mPa.s	7 700
Flash point Cleveland	°C	220
Pour point	°C	-51

The typical characteristics mentioned represent mean values.

PERFORMANCES

DEXRON®-IIE : former licence n° E-25218)
MAN 339 type V-2 (ex MAN 339 Type D)
MAN 339 type Z-2 (ex MAN 339 Type D)
MB-Approval 236.8
VOITH H 55.633635
ZF TE-ML 09X, 14B, 16L

TOTAL LUBRIFIANTS
16, rue de la République
92800 PUTEAUX

FLUIDE SYN FE
Sheet updated: 03/2008
Sticker reference: MPR 09/07



This lubricant, when used in accordance with our recommendations and for the application for which it is intended, does not constitute a special hazard. A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant