

TRANSMISSION SYN FE 75W-140



SYNTHETIC OIL FOR GEARS

USES

- Very high performance synthetic oil for axles and reduction gears.
- High loaded gears.
- Recommended when filters are added to the lubrication system.
- Recommended for axles requiring API GL-5 level.

PROPERTIES

- Very high viscosity index.
- Increased Extreme-Pressure and antiwear properties for an optimized lubrication of hypoid or non-hypoid axles.
- Excellent antifoam, anticorrosion, antirust properties.
- Excellent thermal stability.
- Very low loss in viscosity through shear.
- Excellent stability in service.
- Extended drain interval.
- Fuel saving.

CHARACTERISTICS

| TRANSMISSION SYN FE | Units | Grade SAE 75W-140 |
|-------------------------|--------------------|----------------------|
| Volumetric mass at 15°C | kg/m ³ | 885 |
| Viscosity at - 40°C | mPa.s | 130 000 |
| Viscosity at 40°C | mm ² /s | 183 |
| Viscosity at 100°C | mm ² /s | 26 |
| Viscosity index | - | 178 |
| Pour point | °C | - 36 |

The typical characteristics mentioned represent mean values.

SPECIFICATIONS

API GL-5
SCANIA STO 1:0

TOTAL LUBRIFIANTS
16, rue de la République
92800 PUTEAUX

TRANSMISSION SYN FE 75W-140
Sheet updated : 03/2008
Sticker reference : MPR/07/05



This lubricant, when used in accordance with our recommendations and for the application for which it is intended, does not constitute a special hazard. A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant